



Washing and
disinfection in the
laboratories sector

2009



MACHINES

Basic line - glassware washer 45 cm

GW2050

SINGLE-PHASE LABORATORY GLASSWARE WASHERS

3390 €



SINGLE-PHASE LABORATORY GLASSWARE WASHERS

- WASHING UP TO 95°C - THERMAL DISINFECTION
- 8 PROGRAMME ELECTRONIC PROGRAMMING
- STATIC DRYING
- ALKALINE POWDER DETERGENT DISPENSER AT OPENING
- PERISTALTIC PUMP FOR ACID LIQUID NEUTRALIZER
- EXTERNAL PANELS IN STAINLESS STEEL
- EXTERNAL DIMENSIONS LXWXH (MM) 450X600X850
- INTERNAL WORKING DIMENSIONS LXWXH (MM) 380X480X590
- INCORPORATED WATER SOFTENER
- WATER SUPPLY CONNECTION AND DEMINERALIZED WATER
- ELECTRICAL CONNECTION 1/N/PE 230V 50HZ 3.3KW MAX
- SCHUKO PLUG 16A/250V INCLUDED
- UPPER TROLLEY D-CS1 INCLUDED
- LOWER TROLLEY D-CS2 INCLUDED

Basic line - glassware washer 60 cm

GW1050

THREE-PHASE VERSION LABORATORY GLASSWARE WASHERS

3690 €



THREE-PHASE VERSION LABORATORY GLASSWARE WASHERS

- WASHING UP TO 95°C - THERMAL DISINFECTION
- 8 PROGRAMME ELECTRONIC PROGRAMMING
- STATIC DRYING
- ALKALINE POWDER DETERGENT DISPENSER AT OPENING
- PERISTALTIC PUMP FOR ACID LIQUID NEUTRALIZER
- EXTERNAL PANELS IN STAINLESS STEEL
- EXTERNAL DIMENSIONS LXWXH (MM) 600X640X850
- INTERNAL WORKING DIMENSIONS LXWXH (MM) 520X515X545
- INCORPORATED WATER SOFTENER • WATER SUPPLY CONNECTION AND DEMINERALIZED WATER
- ELECTRICAL CONNECTION 3P+N 400V 50HZ KW 7 MAX
- WITHOUT TROLLEY

GW1050-1

SINGLE-PHASE VERSION LABORATORY GLASSWARE WASHERS

3690 €



SINGLE-PHASE VERSION LABORATORY GLASSWARE WASHERS

- WASHING UP TO 95°C - THERMAL DISINFECTION
- 8 PROGRAMME ELECTRONIC PROGRAMMING
- STATIC DRYING
- ALKALINE POWDER DETERGENT DISPENSER AT OPENING
- PERISTALTIC PUMP FOR ACID LIQUID NEUTRALIZER
- EXTERNAL PANELS IN STAINLESS STEEL
- EXTERNAL DIMENSIONS LXWXH (MM) 600X640X850
- INTERNAL WORKING DIMENSIONS LXWXH (MM) 520X515X545
- INCORPORATED WATER SOFTENER
- WATER SUPPLY CONNECTION AND DEMINERALIZED WATER
- ELECTRICAL CONNECTION 1P+N 230V 50HZ 2,8 KW MAX
- WITHOUT TROLLEY

Professional line - glassware washer 60 cm

GW3060BX

LABORATORY GLASSWARE WASHER

4780 €



LABORATORY GLASSWARE WASHER

- WASHING UP TO 95°C - THERMAL DISINFECTION
- 3 MICROPROCESSOR PROGRAMMABLE ELECTRONICS, UP TO 100 PROGRAMMES
- SERIAL PORT RS232 FOR CONNECTION TO EXTERNAL PRINTER OR PC
- 128X64 PIXEL GRAPHICS DISPLAY
- ACTIVE THERMODYNAMIC DRYING
- POWDER DETERGENT DOSING AT OPENING
- LIQUID NEUTRALIZER DOSING
- EXTERNAL PANELS IN STAINLESS STEEL
- EXTERNAL DIMENSIONS LXWXH (MM) 600X640X850
- INTERNAL WORKING DIMENSIONS LXWXH (MM) 520X515X545
- INCORPORATED WATER SOFTENER - VOLUMETRIC REGENERATION
- WATER SUPPLY CONNECTION, HOT WATER AND DEMINERALIZED WATER
- ELECTRICAL CONNECTION 3P+N 400V 50HZ 7KW MAX (COMMUTABLE SINGLE-PHASE 230V)
- WITHOUT TROLLEY

GW3060S

LABORATORY GLASSWARE WASHER

4930 €



LABORATORY GLASSWARE WASHER

- WASHING UP TO 95°C - THERMAL DISINFECTION
- 3 MICROPROCESSOR PROGRAMMABLE ELECTRONICS, UP TO 100 PROGRAMMES
- 128X64 PIXEL GRAPHICS DISPLAY
- SERIAL PORT RS232 FOR CONNECTION TO EXTERNAL PRINTER OR PC
- ACTIVE THERMODYNAMIC DRYING
- LIQUID DETERGENT DOSAGE PUMP
- LIQUID NEUTRALIZER DOSAGE PUMP
- EXTERNAL PANELS IN STAINLESS STEEL
- EXTERNAL DIMENSIONS LXWXH (MM) 600X640X850
- INTERNAL WORKING DIMENSIONS LXWXH (MM) 520X515X545
- INCORPORATED WATER SOFTENER - VOLUMETRIC REGENERATION
- WATER SUPPLY CONNECTION, HOT WATER AND DEMINERALIZED WATER
- ELECTRICAL CONNECTION 3P+N 400V 50HZ 7KW MAX (COMMUTABLE SINGLE-PHASE 230V)
- WITHOUT TROLLEY

GW3060P

LABORATORY GLASSWARE WASHER - PETROL

5250 €



LABORATORY GLASSWARE WASHER - PETROL

- WASHING UP TO 95°C - THERMAL DISINFECTION
- 3 MICROPROCESSOR PROGRAMMABLE ELECTRONICS, UP TO 100 PROGRAMMES
- 128X64 PIXEL GRAPHICS DISPLAY
- SERIAL PORT RS232 FOR CONNECTION TO EXTERNAL PRINTER OR PC
- ACTIVE THERMODYNAMIC DRYING
- LIQUID DETERGENT DOSAGE PUMP
- LIQUID NEUTRALIZER DOSAGE PUMP
- 2 SUPPLEMENTARY PUMPS FOR WASHING ADDITIVES
- EXTERNAL PANELS IN STAINLESS STEEL
- EXTERNAL DIMENSIONS LXWXH (MM) 600X640X850
- INTERNAL WORKING DIMENSIONS LXWXH (MM) 520X515X545
- INCORPORATED WATER SOFTENER - VOLUMETRIC REGENERATION
- WATER SUPPLY CONNECTION, HOT WATER AND DEMINERALIZED WATER
- ELECTRICAL CONNECTION 3P+N 400V 50HZ 7KW MAX (COMMUTABLE SINGLE-PHASE 230V)
- WITHOUT TROLLEYS

Professional line - glassware washer 90 cm

GW4090

LABORATORY GLASSWARE WASHER - DRYING SYSTEM

7280 €



LABORATORY GLASSWARE WASHER - DRYING SYSTEM

- WASHING UP TO 95°C - THERMAL DISINFECTION
- 3 MICROPROCESSOR PROGRAMMABLE ELECTRONICS, UP TO 100 PROGRAMMES
- 128X64 PIXEL GRAPHICS DISPLAY
- SERIAL PORT RS232 FOR CONNECTION TO EXTERNAL PRINTER OR PC
- FORCED HOT AIR DRYING SYSTEM WITH AIR FILTER 98% DOP
- LIQUID DETERGENT DOSAGE PUMP
- LIQUID NEUTRALIZER DOSAGE PUMP
- EXTERNAL PANELS IN STAINLESS STEEL
- DETERGENT CABINET
- EXTERNAL DIMENSIONS LXWXH (MM) 900X640X850
- INTERNAL WORKING DIMENSIONS LXWXH (MM) 520X515X545
- INCORPORATED WATER SOFTENER – VOLUMETRIC REGENERATION
- WATER SUPPLY CONNECTION, HOT WATER AND DEMINERALIZED WATER
- ELECTRICAL CONNECTION 3P+N 400V 50HZ 7KW MAX (COMMUTABLE SINGLE-PHASE 230V)
- WITHOUT TROLLEY

GW4090C

**LABORATORY GLASSWARE WASHER - DRYING SYSTEM AND
VAPOUR CONDENSER**

7870 €



LABORATORY GLASSWARE WASHER - DRYING SYSTEM AND VAPOUR CONDENSER

- WASHING UP TO 95°C - THERMAL DISINFECTION
- 3 MICROPROCESSOR PROGRAMMABLE ELECTRONICS, UP TO 100 PROGRAMMES
- 128X64 PIXEL GRAPHICS DISPLAY
- SERIAL PORT RS232 FOR CONNECTION TO EXTERNAL PRINTER OR PC
- FORCED HOT AIR DRYING SYSTEM WITH AIR FILTER 98% DOP
- REMOVAL VAPOUR CONDENSER
- LIQUID DETERGENT DOSAGE PUMP
- LIQUID NEUTRALIZER DOSAGE PUMP
- EXTERNAL PANELS IN STAINLESS STEEL
- DETERGENT CABINET
- EXTERNAL DIMENSIONS LXWXH (MM) 900X640X850
- INTERNAL WORKING DIMENSIONS LXWXH (MM) 520X515X545
- INCORPORATED WATER SOFTENER – VOLUMETRIC REGENERATION
- WATER SUPPLY CONNECTION, HOT WATER AND DEMINERALIZED WATER
- ELECTRICAL CONNECTION 3P+N 400V 50HZ 7KW MAX (COMMUTABLE SINGLE-PHASE 230V)
- WITHOUT TROLLEYS

Professional line - large dimension glassware washers

GW6090

HIGH CAPACITY LABORATORY GLASSWARE WASHER

21450 €



HIGH CAPACITY LABORATORY GLASSWARE WASHER

- WASHING UP TO 95°C - THERMAL DISINFECTION
- WASHING ON 3 LEVELS
- 3 MICROPROCESSOR PROGRAMMABLE ELECTRONICS, UP TO 100 PROGRAMMES
- 128X64 PIXEL GRAPHICS DISPLAY
- SERIAL PORT RS232 FOR CONNECTION TO EXTERNAL PRINTER OR PC
- ACTIVE THERMODYNAMIC DRYING
- LIQUID DETERGENT DOSAGE PUMP
- LIQUID NEUTRALIZER DOSAGE PUMP
- 2 SUPPLEMENTARY PUMPS FOR WASHING ADDITIVES
- EXTERNAL PANELS IN STAINLESS STEEL
- DETERGENT CABINET FOR 4 5L CANS
- EXTERNAL DIMENSIONS LXWXH (MM) 900X800X1900
- INTERNAL WORKING DIMENSIONS LXWXH (MM) 670X650X835
- BUILT-IN BOILER FOR PREHEATING WATER
- WATER SUPPLY CONNECTION, HOT WATER AND DEMINERALIZED WATER
- ELECTRICAL CONNECTION 3P+N 400V 50HZ 18KW MAX

GW6090DS

HIGH CAPACITY LABORATORY GLASSWARE WASHER – DRYING SYSTEM

26900 €



HIGH CAPACITY LABORATORY GLASSWARE WASHER – DRYING SYSTEM

- WASHING UP TO 95°C - THERMAL DISINFECTION
- WASHING ON 3 LEVELS
- 3 MICROPROCESSOR PROGRAMMABLE ELECTRONICS, UP TO 100 PROGRAMMES
- 128X64 PIXEL GRAPHICS DISPLAY
- SERIAL PORT RS232 FOR CONNECTION TO EXTERNAL PRINTER OR PC
- DOUBLE FORCED HOT AIR DRYING SYSTEM
- ABSOLUTE DRYING FILTER 99.999% HEPA
- LIQUID DETERGENT DOSAGE PUMP
- LIQUID NEUTRALIZER DOSAGE PUMP
- 2 SUPPLEMENTARY PUMPS FOR WASHING ADDITIVES
- EXTERNAL PANELS IN STAINLESS STEEL
- DETERGENT CABINET FOR 4 5L CANS
- EXTERNAL DIMENSIONS LXWXH (MM) 900X800X2100
- INTERNAL WORKING DIMENSIONS LXWXH (MM) 670X650X835
- BUILT-IN BOILER FOR PREHEATING WATER
- WATER SUPPLY CONNECTION, HOT WATER AND DEMINERALIZED WATER
- ELECTRICAL CONNECTION 3P+N 400V 50HZ 18KW MAX
- WITHOUT TROLLEYS

MACHINE ACCESSORIES

Base trolleys

D-CS1

UPPER TROLLEY WITH SPRAYER

177 €



UPPER TROLLEY WITH SPRAYER
 • SUITABLE FOR HOLDING OF SUPPORTS AND BASKETS
 • MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X							
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

D-CS2

LOWER TROLLEY

138 €



LOWER TROLLEY
 • SUITABLE FOR HOLDING OF SUPPORTS AND BASKETS
 • MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X							
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

CS1-1

UPPER TROLLEY WITH SPRAYER

187 €



UPPER TROLLEY WITH SPRAYER
 • SUITABLE FOR HOLDING OF SUPPORTS AND BASKETS
 • MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

CS2

LOWER TROLLEY

162 €



LOWER TROLLEY
 • SUITABLE FOR HOLDING OF SUPPORTS AND BASKETS
 • MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

Flask and beaker supports

SB9

9 POSITION BEAKER SUPPORT

115 €



9 POSITION BEAKER SUPPORT

- FOR CYLINDERS OF MAX 100 ML AND FUNNELS
- DIMENSIONS : L X W X H = 420 X 145 X 160 MM
- OCCUPIES 1/2 TROLLEYS D-CS1 / D-CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

SB14

SPRING SUPPORT - 14 POSITIONS

115 €



SPRING SUPPORT - 14 POSITIONS

- FOR BEAKERS / ERLNMEYER FLASKS FROM 250 TO 1000 ML
- DIMENSIONS : L X W X H = 422 X 146 X 184 MM
- OCCUPIES 1/2 TROLLEY D-CS1 / D- CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X							
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

SB15

SPRING SUPPORT - 16 POSITIONS

119 €



SPRING SUPPORT - 16 POSITIONS

- FOR BEAKERS / ERLNMEYER FLASKS FROM 500 TO 1000 ML
- DIMENSIONS : L X W X H = 195 X 40 X 185 MM
- OCCUPIES 1/2 TROLLEY CS1-1 / CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

SB25

SPRING SUPPORT - 28 POSITIONS

119 €



SPRING SUPPORT - 28 POSITIONS

- FOR BEAKERS / ERLNMEYER FLASKS FROM 250 TO 500 ML
- DIMENSIONS : L X W X H = 195 X 40 X 115 MM
- OCCUPIES 1/2 TROLLEY CS1-1 / CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

SB28

SPRING SUPPORT - 28 POSITIONS

119 €



SPRING SUPPORT - 28 POSITIONS

- FOR BEAKERS / ERLNMEYER FLASKS FROM 250 TO 1000 ML
- DIMENSIONS : L X W X H = 195 X 40 X 185 MM
- OCCUPIES 1/2 TROLLEY CS1-1 / CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

SB30**30 POSITION BEAKERS SUPPORT****173 €****30 POSITION BEAKERS SUPPORT**

- FOR CYLINDERS OF MAX 100 ML AND FUNNELS
- DIMENSIONS : L X W X H = 195 X 40 X 150 MM
- OCCUPIES 1/2 TROLLEY CS1-1 / CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

Plate and slide supports**SL9****SUPPORT FOR CHROMATOGRAPHY PLATES****132 €****SUPPORT FOR CHROMATOGRAPHY PLATES**

- SUITABLE FOR HOLDING UP TO 9 PLATES MEASURING FROM 150X150 MM TO 220X220MM
- DIMENSIONS : L X W X H = 395 X 195 X 110 MM
- OCCUPIES 1/2 TROLLEY CS1-1 / CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

SL18**BASKET WITH SUPPORT FOR CHROMATOGRAPHY PLATES****289 €****BASKET WITH SUPPORT FOR CHROMATOGRAPHY PLATES**

- SUITABLE FOR HOLDING UP TO 18 PLATES 200X200 MM
- DIMENSIONS : L X W X H = 465 X 215 X 130 MM
- OCCUPIES 1/2 TROLLEY CS1-1 / CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

PV105**MICROSCOPY SLIDE BASKET****100 €****MICROSCOPY SLIDE BASKET**

- SUITABLE FOR HOLDING 105 STANDARD SLIDES FOR MICROSCOPY
- MADE IN STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

PB250**SUPPORT FOR 250 ML WIDE NECK BOTTLES****286 €****SUPPORT FOR 250 ML WIDE NECK BOTTLES**

- CAPACITY 24 250 ML WIDE NECK BOTTLES (SCREW CAP GL45 ISO4796 OR SOCKET DIN 12038 OR NON-NORMALIZED).
- MAX BOTTLE DIMENSIONS: DIAM. 70 MM - H 138 MM.
- POSITIONED ON LOWER TROLLEY CS2
- MADE IN STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

PB500**SUPPORT FOR 500 ml WIDE NECK BOTTLES****286 €**

SUPPORT FOR 500 ml WIDE NECK BOTTLES

- CAPACITY 21 500 ML WIDE NECK BOTTLES (SCREW CAP GL45 ISO4796 OR SOCKET DIN 12038 OR NON-NORMALIZED).
- MAX BOTTLE DIMENSIONS: DIAM. 86 MM - H 176 MM.
- POSITIONED ON LOWER TROLLEY CS2
- MADE IN STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

PB1000**SUPPORT FOR 1000 ml WIDE NECK BOTTLES****286 €**

SUPPORT FOR 1000 ml WIDE NECK BOTTLES

- CAPACITY 16 1000 ML WIDE NECK BOTTLES (SCREW CAP GL45 ISO4796 OR SOCKET DIN 12038 OR NON-NORMALIZED)
- MAX BOTTLE DIMENSIONS: DIAM. 101 MM - H 225 MM.
- POSITIONED ON LOWER TROLLEY CS2
- MADE IN STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

Test tube supports

CP105**TEST TUBE BASKET - H = 75 MM****176 €**

TEST TUBE BASKET - H = 75 MM

- CAPACITY 160 STANDARD TEST TUBES
- EQUIPPED WITH 2 REMOVABLE COMPARTMENTS WITH LID
- OCCUPIES 1/2 TROLLEY D-CS2
- OCCUPIES 1/4 TROLLEY CS1-1 / CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

CP132**TEST TUBE BASKET - H = 105 MM****181 €**

TEST TUBE BASKET - H = 105 MM

- CAPACITY 160 STANDARD TEST TUBES
- EQUIPPED WITH 2 REMOVABLE COMPARTMENTS WITH LID
- OCCUPIES 1/2 TROLLEY D-CS2
- OCCUPIES 1/4 TROLLEY CS1-1 / CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

CP192**TEST TUBE BASKET - H = 165 MM****200 €**

TEST TUBE BASKET - H = 165 MM

- CAPACITY 160 STANDARD TEST TUBES
- EQUIPPED WITH 2 REMOVABLE COMPARTMENTS WITH LID
- OCCUPIES 1/2 TROLLEY D-CS2
- OCCUPIES 1/4 TROLLEY CS1-1 / CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

CP222**TEST TUBE BASKET - H = 200 MM****215 €**

TEST TUBE BASKET - H = 200 MM

- CAPACITY 160 STANDARD TEST TUBES
- EQUIPPED WITH 2 REMOVABLE COMPARTMENTS WITH LID
- OCCUPIES 1/2 TROLLEY D-CS2
- OCCUPIES 1/4 TROLLEY CS1-1 / CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

Petri dish supports

PD70I**LOWER SUPPORT FOR PETRI DISHES 50-70 MM****341 €**

LOWER SUPPORT FOR PETRI DISHES 50-70 MM

- CAPACITY 42 PIECES
- DIMENSIONS : L X W = 456 X 460 MM
- POSITIONED ON LOWER TROLLEY CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

PD70S**UPPER SUPPORT FOR PETRI DISHES 50-70 MM****341 €**

UPPER SUPPORT FOR PETRI DISHES 50-70 MM

- CAPACITY 40 PIECES
- DIMENSIONS : L X W = 456 X 460 MM
- POSITIONED ON UPPER TROLLEY CS1-1 OR ON SUPPORTS PD70 I / PD100 I
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

PD100I**LOWER SUPPORT FOR PETRI DISHES 70-120 MM****341 €**

LOWER SUPPORT FOR PETRI DISHES 70-120 MM

- CAPACITY 42 PIECES
- DIMENSIONS : L X W = 456 X 460 MM
- POSITIONED ON LOWER TROLLEY CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

PD100S**UPPER SUPPORT FOR PETRI DISHES 70-120 MM****341 €**

UPPER SUPPORT FOR PETRI DISHES 70-120 MM

- CAPACITY 38 PIECES
- DIMENSIONS : L X W = 456 X 460 MM
- POSITIONED ON UPPER TROLLEY CS1-1 OR ON SUPPORTS PD70 I / PD100 I
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

Bottom racks for small glassware, baskets and netting

D-PF1**COMPLETE STAINLESS STEEL BOTTOM FOR UPPER TROLLEY****115 €**

COMPLETE STAINLESS STEEL BOTTOM FOR UPPER TROLLEY

- MADE OF STAINLESS STEEL MESH NETTING WITH CENTRAL HOLE - MESH = 10 x 10 MM
- DIM.: L X W X H = 305 x 425 x 11 MM
- POSITIONED ON UPPER TROLLEY D-CS1

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X							
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

D-PF2**COMPLETE STAINLESS STEEL BOTTOM FOR LOWER TROLLEY****115 €**

COMPLETE STAINLESS STEEL BOTTOM FOR LOWER TROLLEY

- MADE OF STAINLESS STEEL NETTING - MESH = 10 x 10 MM
- DIM.: L X W X H = 305 x 425 x 11 MM
- POSITIONED ON LOWER TROLLEY D-CS2

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X							
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

PF1

COMPLETE STAINLESS STEEL BOTTOM FOR UPPER TROLLEY

115 €



COMPLETE STAINLESS STEEL BOTTOM FOR UPPER TROLLEY
 • MADE OF STAINLESS STEEL MESH NETTING WITH CENTRAL HOLE - MESH = 10 x 10 MM
 • DIMENSIONS: L X W X H = 454 x 434 x 11 MM
 • POSITIONED ON UPPER TROLLEY CS1-1

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

PF1/2

HALF STAINLESS STEEL BOTTOM BASKET

92 €



HALF STAINLESS STEEL BOTTOM BASKET
 • MADE OF STAINLESS STEEL MESH NETTING- MESH = 10 x 10 MM
 • DIMENSIONS: L X W X H = 224 x 434 x 11 MM

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

RC1/4

GLASSWARE FIXING NET

47 €



GLASSWARE FIXING NET
 • MESH IN NYLON 10 x 10 MM
 • DIMENSIONS : L X W = 204 x 204 MM
 • OCCUPIES 1/4 TROLLEYS CS1-1 / CS2

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

PF2

COMPLETE STAINLESS STEEL BOTTOM FOR LOWER TROLLEY

127 €



COMPLETE STAINLESS STEEL BOTTOM FOR LOWER TROLLEY
 • MADE OF STAINLESS STEEL MESH NETTING - MESH = 10 x 10 MM
 • DIMENSIONS: L X W X H = 454 x 434 x 11 MM
 • POSITIONED ON LOWER TROLLEY CS2

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

RC1

COMPLETE GLASSWARE FIXING NET

81 €



COMPLETE GLASSWARE FIXING NET
 • MESH IN NYLON 25 x 25 MM
 • DIMENSIONS : L X W = 474 x 516 MM
 • POSITIONED ON LOWER TROLLEY CS2

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

RC1/2

GLASSWARE FIXING NET

64 €



GLASSWARE FIXING NET

- MESH IN NYLON 25 x 25 MM
- DIMENSIONS : L X W = 456 x 214 MM
- OCCUPIES 1/2 TROLLEYS CS1-1 / CS2

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

Supports for injection washing

LM22S

UPPER UNIVERSAL FLASK WASHING – 22 POSITIONS

799 €



UPPER UNIVERSAL FLASK WASHING – 22 POSITIONS

- SUITABLE FOR WASHING NARROW-NECKED GLASSWARE UP TO 225MM IN HEIGHT
- EQUIPPED WITH THE FOLLOWING NOZZLES : 12 X U4140, 5 X U3110, 5 X U390
- POSITIONED ON THE UPPER TROLLEY LEVEL D-CS1
- MADE IN STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X							
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LM24

UNIVERSAL FLASK WASHING - 24 POSITIONS

799 €



UNIVERSAL FLASK WASHING - 24 POSITIONS

- SUITABLE FOR WASHING NARROW-NECKED GLASSWARE UP TO 490MM IN HEIGHT
- EQUIPPED WITH THE FOLLOWING NOZZLES: 6 X U6240, 5 X U6220, 6 X U4160, 5 X U4140, 2 X U3110
- POSITIONED ON THE LOWER TROLLEY LEVEL D-CS2
- MADE IN STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X							
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LPM24

PIPETTES/FLASK WASHING TROLLEY - 12+12 POSITIONS

778 €



PIPETTES/FLASK WASHING TROLLEY - 12+12 POSITIONS

- SUITABLE FOR WASHING NARROW-NECKED GLASSWARE E PIPETTES UP TO 490MM IN HEIGHT
- EQUIPPED WITH THE FOLLOWING NOZZLES : 4 X U6240, 2 X U6220, 2 X U4160, 2 X U4140, 2 X U3110, 12 X LB40
- MAXIMUM GLASSWARE HEIGHT 490 MM • POSITIONED ON THE LOWER TROLLEY LEVEL D-CS2
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X							
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

Narrow neck glassware injection trolleys

LM20

UNIVERSAL FLASK WASHING - 20 POSITIONS

853 €



UNIVERSAL FLASK WASHING - 20 POSITIONS

- SUITABLE FOR WASHING NARROW-NECKED GLASSWARE UP TO 490MM IN HEIGHT
- EQUIPPED WITH THE FOLLOWING NOZZLES : 2 x U6260, 2 x U6240, 2 x U6220, 3 x U4180, 2 x U4160, 2 x U4140, 3 x U3110, 4 x U390, 1 x UC6
- HALF TROLLEY FOR FREE LOADING, TO BE COMPLETED WITH TEST TUBE BASKETS , Erlenmeyer flask supports , BASKETS CPF1/2 AND CSK2 • POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LM20DS

UNIVERSAL FLASK WASHING WITH DRYING SYSTEM - 20 POSITIONS

1110 €



UNIVERSAL FLASK WASHING WITH DRYING SYSTEM - 20 POSITIONS

- SUITABLE FOR WASHING AND DRYING OF NARROW NECK GLASSWARE UP TO 490MM IN HEIGHT
- EQUIPPED WITH THE FOLLOWING NOZZLES : 2 x U6260, 2 x U6240, 2 x U6220, 3 x U4180, 2 x U4160, 2 x U4140, 3 x U3110, 4 x U390, 1 x UC6 • HALF TROLLEY FOR FREE LOADING, TO BE COMPLETED WITH TEST TUBE BASKETS , Erlenmeyer flask supports , BASKETS CPF1/2 AND CSK2 • POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
						X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LM40

UNIVERSAL FLASK WASHING - 40 POSITIONS

853 €



UNIVERSAL FLASK WASHING - 40 POSITIONS

- SUITABLE FOR WASHING NARROW-NECKED GLASSWARE UP TO 490MM IN HEIGHT
- EQUIPPED WITH THE FOLLOWING NOZZLES : 5 x U6260, 5 x U6240, 5 x U6220, 5 x U4180, 5 x U4160, 5 x U4140, 5 x U3110, 5 x U390, 1 x UC6
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LM40DS

UNIVERSAL FLASK WASHING WITH DRYING SYSTEM- 40 POSITIONS

1020 €



UNIVERSAL FLASK WASHING WITH DRYING SYSTEM- 40 POSITIONS

- SUITABLE FOR WASHING AND DRYING OF NARROW NECK GLASSWARE UP TO 490MM IN HEIGHT
- EQUIPPED WITH THE FOLLOWING NOZZLES: 5 x U6260, 5 x U6240, 5 x U6220, 5 x U4180, 5 x U4160, 5 x U4140, 5 x U3110, 5 x U390, 1 x UC6
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
						X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LM40S**UPPER FLASK WASHING - 40 POSITIONS****875 €****UPPER FLASK WASHING - 40 POSITIONS**

- SUITABLE FOR WASHING NARROW-NECKED GLASSWARE UP TO 225MM IN HEIGHT
- EQUIPPED WITH 40 NOZZLES U4140
- POSITIONED ON THE UPPER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LM40SDS**UPPER FLASK WASHING WITH DRYING SYSTEM - 40 POSITIONS****1040 €****UPPER FLASK WASHING WITH DRYING SYSTEM - 40 POSITIONS**

- SUITABLE FOR WASHING AND DRYING OF NARROW NECK GLASSWARE UP TO 225MM IN HEIGHT
- EQUIPPED WITH 40 NOZZLES U4140
- POSITIONED ON THE UPPER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LM80**UNIVERSAL FLASK WASHING, TWO WASHING LEVELS****1630 €****UNIVERSAL FLASK WASHING, TWO WASHING LEVELS**

- SUITABLE FOR WASHING NARROW-NECKED GLASSWARE UP TO 225MM IN HEIGHT
- CAPACITY 68 PIECES
- EQUIPPED WITH 68 NOZZLES U4140, 1 NOZZLE UC6
- POSITIONED ON 2 LEVELS
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LM80DS**UNIVERSAL FLASK WASHING WITH DRYING SYSTEM - TWO WASHING LEVELS****1740 €****UNIVERSAL FLASK WASHING WITH DRYING SYSTEM - TWO WASHING LEVELS**

- SUITABLE FOR WASHING AND DRYING OF NARROW NECK GLASSWARE UP TO 225MM IN HEIGHT
- CAPACITY 68 PIECES
- EQUIPPED WITH 68 NOZZLES U4140 + 1 NOZZLE UC6
- POSITIONED ON 2 LEVELS
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LR4**REACTOR WASHING TROLLEY****1240 €****REACTOR WASHING TROLLEY**

- SUITABLE FOR WASHING 4 REACTORS WITH 3 / 5 NECKS OF 3 LITERS MAX OR UP TO 12 PIECES OF NARROW NECK GLASSWARE
- EQUIPPED WITH 12 NOZZLES U6260
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LR4DS**REACTOR WASHING TROLLEY WITH DRYING SYSTEM****1380 €****REACTOR WASHING TROLLEY WITH DRYING SYSTEM**

- SUITABLE FOR WASHING AND DRYING OF 4 REACTORS WITH 3 / 5 NECKS OF 3 LITERS MAX OR UP TO 12 PIECES OF NARROW NECK GLASSWARE
- EQUIPPED WITH 12 NOZZLES U6260
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
						X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LT20**TROLLEY FOR FISCHER TUBES****1240 €****TROLLEY FOR FISCHER TUBES**

- SUITABLE FOR WASHING OF 12 FISCHER TUBES MAX HEIGHT 55 CM AND 6 PIECES OF NARROW NECK GLASSWARE
- EQUIPPED WITH THE FOLLOWING NOZZLES : 12 x U6370, 2 x U6220, 2 x U4160, 2 x U390
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LT20DS**TROLLEY FOR FISCHER TUBES WITH DRYING SYSTEM****1380 €****TROLLEY FOR FISCHER TUBES WITH DRYING SYSTEM**

- SUITABLE FOR WASHING AND DRYING OF 12 FISCHER TUBES MAX HEIGHT 55 CM AND 6 PIECES OF NARROW-NECK GLASSWARE
- EQUIPPED WITH THE FOLLOWING NOZZLES : 12 x U6370, 2 x U6220, 2 x U4160, 2 x U390
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
						X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LBT5**TROLLEY FOR BOTTLES****1220 €****TROLLEY FOR BOTTLES**

- SUITABLE FOR WASHING 5 5-LITER BOTTLES (D 180 X H 500MM, D. NECK MAX 80 MM)
- EQUIPPED WITH 5 SPECIAL NOZZLES
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LBT5DS**TROLLEY FOR BOTTLES WITH DRYING SYSTEM****1380 €****TROLLEY FOR BOTTLES WITH DRYING SYSTEM**

- SUITABLE FOR WASHING AND DRYING 5 5-LITER BOTTLES (D 180 X H 500MM, D. NECK MAX 80 MM)
- EQUIPPED WITH 5 SPECIAL NOZZLES
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
						X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LB16**LOWER INJECTION TROLLEY FOR BOTTLES****1150 €****LOWER INJECTION TROLLEY FOR BOTTLES**

- SUITABLE FOR WASHING 16 PIECES TO BE CHOSEN BETWEEN :
NARROW-NECK BOTTLES / WIDE 250-1000 ML. WITH DIM. MAX : DIAM. 101 MM - H 450 MM
BURETTE FLASKS 2000 ML DIAM. MAX 160 MM - H 200 MM
GRADUATED CYLINDERS DIAM. MAX 101 MM - H 495 MM
- EQUIPPED WITH 16 NOZZLES U6170
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LB16-DS**LOWER INJECTION TROLLEY FOR BOTTLES WITH DRYING SYSTEM****1380 €****LOWER INJECTION TROLLEY FOR BOTTLES WITH DRYING SYSTEM**

- SUITABLE FOR WASHING AND DRYING 16 PIECES TO BE CHOSEN BETWEEN :
NARROW-NECK BOTTLES / WIDE 250-1000 ML. DIM. MAX : DIAM. 101 MM - H 450 MM
BURETTE FLASKS 2000 ML DIAM. MAX 160 MM - H 200 MM
GRADUATED CYLINDERS DIAM. MAX 101 MM - H 495 MM
- EQUIPPED WITH 16 NOZZLES U6170
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LB32**TWO LEVEL INJECTION TROLLEY FOR BOTTLES****2290 €****TWO LEVEL INJECTION TROLLEY FOR BOTTLES**

- SUITABLE FOR WASHING 32 NARROW-NECK BOTTLES / WIDE 250-1000 ML. DIAM. MAX 101 MM - H 245 MM
- EQUIPPED WITH 32 NOZZLES U6170
- POSITIONED ON 2 LEVELS
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LB32DS**TWO LEVEL INJECTION TROLLEY FOR BOTTLES WITH DRYING SYSTEM****2740 €****TWO LEVEL INJECTION TROLLEY FOR BOTTLES WITH DRYING SYSTEM**

- SUITABLE FOR WASHING AND DRYING 32 NARROW-NECK BOTTLES / WIDE 250-1000 ML. DIAM. MAX 101 MM - H 245 MM
- EQUIPPED WITH 32 NOZZLES U6170
- POSITIONED ON 2 LEVELS
- MADE OF STAINLESS

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
						X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LB40**TROLLEY FOR BUTYROMETERS****1440 €****TROLLEY FOR BUTYROMETERS**

- SUITABLE FOR WASHING 40 BUTYROMETERS
- SPECIFY THE TYPE OF BUTYROMETERS WHEN ORDERING
- POSITIONED ON THE UPPER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LB40DS**TROLLEY FOR BUTYROMETERS WITH DRYING SYSTEM****1630 €****TROLLEY FOR BUTYROMETERS WITH DRYING SYSTEM**

- SUITABLE FOR WASHING AND DRYING 40 BUTYROMETERS
- SPECIFY THE TYPE OF BUTYROMETERS WHEN ORDERING
- POSITIONED ON THE UPPER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
						X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

Pipette injection trolleys**LPV40****PIPETTE WASHER TROLLEY****932 €****PIPETTE WASHER TROLLEY**

- SUITABLE FOR WASHING 20 VOLUMETRIC PIPETTES MAX HEIGHT 55 CM + 20 STANDARD PIPETTES MAX HEIGHT 49 CM
- EQUIPPED WITH 5 SPECIAL NOZZLES
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LPV40DS**PIPETTE WASHER TROLLEY WITH DRYING SYSTEM****1260 €****PIPETTE WASHER TROLLEY WITH DRYING SYSTEM**

- SUITABLE FOR WASHING AND DRYING 20 VOLUMETRIC PIPETTES MAX HEIGHT 55 CM + 20 STANDARD PIPETTES MAX HEIGHT 49 CM
- EQUIPPED WITH 5 SPECIAL NOZZLES
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
						X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LPT100**PIPETTE WASHER TROLLEY****960 €**

PIPETTE WASHER TROLLEY

- SUITABLE FOR WASHING 100 STANDARD PIPETTES MAX HEIGHT 45 CM
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LPT100DS**PIPETTE WASHER TROLLEY WITH DRYING SYSTEM****1120 €**

PIPETTE WASHER TROLLEY WITH DRYING SYSTEM

- SUITABLE FOR WASHING AND DRYING 100 STANDARD PIPETTES MAX HEIGHT 45 CM
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
						X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

Mixed injection trolleys (pipettes + narrow neck)**LPM20-10P****WASHING TROLLEY FOR FLASKS / PIPETTES / TEST TUBES - 20 POSITIONS****982 €**

WASHING TROLLEY FOR FLASKS / PIPETTES / TEST TUBES - 20 POSITIONS

- SUITABLE FOR WASHING 10 PIPETTES UP TO 55 CM + 20 PIECES OF NARROW-NECK GLASSWARE + ¼ FREE RACK, TO BE COMPLETED WITH A TEST TUBE HOLDING BASKETS OF THE CP SERIES
- EQUIPPED WITH THE FOLLOWING NOZZLES : 2 x U6260, 2 x U6240, 2 x U6220, 3 x U4180, 2 x U4160, 2 x U4140, 3 x U3110, 4 x U390, 1 x UC6, 10 x ULB40 FOR PIPETTES MAX HEIGHT 55 CM
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LPM2010DS**WASHING TROLLEY FOR FLASKS / PIPETTES / TEST TUBES - 20 POSITIONS WITH DRYING SYSTEM****1160 €**

WASHING TROLLEY FOR FLASKS / PIPETTES / TEST TUBES - 20 POSITIONS WITH DRYING SYSTEM

- SUITABLE FOR WASHING AND DRYING 10 PIPETTES UP TO 55 CM + 20 PIECES OF NARROW-NECK GLASSWARE + ¼ FREE RACK, TO BE COMPLETED WITH A TEST TUBE HOLDING BASKETS OF THE CP SERIES
- EQUIPPED WITH THE FOLLOWING NOZZLES : 2 x U6260, 2 x U6240, 2 x U6220, 3 x U4180, 2 x U4160, 2 x U4140, 3 x U3110, 4 x U390, 1 x UC6, 10 x ULB40 FOR PIPETTES MAX HEIGHT 55 CM
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
						X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LPM20/20**JET TROLLEY FOR FLASKS / PIPETTES – 20 POSITIONS****982 €**

MIXED WASHING TROLLEY FLASKS / PIPETTES – 20 + 20 POSITIONS

- SUITABLE FOR WASHING 20 PIPETTES UP TO 55 CM + 20 PIECES OF NARROW-NECK GLASSWARE EQUIPPED WITH THE FOLLOWING NOZZLES :
- EQUIPPED WITH THE FOLLOWING NOZZLES : 2 x U6260, 2 x U6240, 2 x U6220, 3 x U4180, 2 x U4160, 2 x U4140, 3 x U3110, 4 x U390, 1 x UC6, 20 x ULB40 FOR PIPETTES MAX HEIGHT 55 CM
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

LPM2020DS**MIXED WASHING TROLLEY FLASKS / PIPETTES – 20 + 20 POSITIONS WITH DRYING SYSTEM****1160 €**

MIXED WASHING TROLLEY FLASKS / PIPETTES – 20 + 20 POSITIONS WITH DRYING SYSTEM

- SUITABLE FOR WASHING AND DRYING 20 PIPETTES UP TO 55 CM + 20 PIECES OF NARROW-NECK GLASSWARE EQUIPPED WITH THE FOLLOWING NOZZLES :
- EQUIPPED WITH THE FOLLOWING NOZZLES : 2 x U6260, 2 x U6240, 2 x U6220, 3 x U4180, 2 x U4160, 2 x U4140, 3 x U3110, 4 x U390, 1 x UC6, 20 x ULB40 FOR PIPETTES MAX HEIGHT 55 CM
- POSITIONED ON LOWER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
						X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

Vials, conical centrifuge test tubes**KP60****UPPER INJECTION TROLLEY FOR TEST TUBES****977 €**

UPPER INJECTION TROLLEY FOR TEST TUBES

- SUITABLE FOR INTERNAL WASHING OF VIALS, CONICAL CENTRIFUGE TUBES, CENTRIFUGE ROTORS
- EQUIPPED WITH 60 NOZZLES U390
- POSITIONED ON UPPER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
X							
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

KP100**UPPER INJECTION TROLLEY FOR TEST TUBES****1590 €**

UPPER INJECTION TROLLEY FOR TEST TUBES

- SUITABLE FOR INTERNAL WASHING OF VIALS, CONICAL CENTRIFUGE TUBES, CENTRIFUGE ROTORS
- EQUIPPED WITH 100 NOZZLES U390
- POSITIONED ON UPPER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WS8	WS8CAB	WS18	WS18CAB

KP100DS**UPPER INJECTION TROLLEY FOR TEST TUBES WITH DRYING SYSTEM****1780 €**

UPPER INJECTION TROLLEY FOR TEST TUBES WITH DRYING SYSTEM

- SUITABLE FOR INTERNAL WASHING AND DRYING OF VIALS, CONICAL CENTRIFUGE TUBES, CENTRIFUGE ROTORS
- EQUIPPED WITH 100 NOZZLES U390
- POSITIONED ON UPPER LEVEL
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
						X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WSB	WS8CAB	WS18	WS18CAB

KP200**TWO LEVEL INJECTION TROLLEY FOR TEST TUBES****2900 €**

TWO LEVEL INJECTION TROLLEY FOR TEST TUBES

- SUITABLE FOR INTERNAL WASHING OF VIALS, CONICAL CENTRIFUGE TUBES, CENTRIFUGE ROTORS
- EQUIPPED WITH 200 NOZZLES U390
- POSITIONED ON TWO LEVELS
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X		
GW6090	GW6090DS	GW6090DSV	WP3000	WSB	WS8CAB	WS18	WS18CAB

Baskets**CPF1****COMPLETE STAINLESS STEEL BOTTOM BASKET WITH EDGE AND HANDLES****166 €**

COMPLETE STAINLESS STEEL BOTTOM BASKET WITH EDGE AND HANDLES

- MADE OF STAINLESS STEEL MESH NETTING - MESH = 10 x 10 MM
- DIM.: L X W X H = 445 x 444 x 68 MM (HEIGHT WITH HANDLE 110 MM)
- POSITIONED ON LOWER TROLLEY CS2

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WSB	WS8CAB	WS18	WS18CAB

CPF1/2**STAINLESS STEEL BOTTOM BASKET WITH EDGE AND HANDLES****127 €**

STAINLESS STEEL BOTTOM BASKET WITH EDGE AND HANDLES

- MADE OF STAINLESS STEEL MESH NETTING - MESH = 10 x 10 MM
- DIM.: L X W X H = 225 x 444 x 68 MM (HEIGHT WITH HANDLE 110 MM)
- OCCUPIES 1/2 LOWER TROLLEY CS2

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WSB	WS8CAB	WS18	WS18CAB

CSK2**BASKET WITH HANDLES****125 €**

BASKET WITH HANDLES

- SUITABLE FOR HOLDING MEDIUM-SIZED INSTRUMENTS
- DIMENSIONS : L X W X H = 450 x 225 x 50 MM
- IN 5 X 5 MM MESH
- MADE OF STAINLESS STEEL

GW2050	GW1050-1	GW1050	GW3060BX	GW3060S	GW3060P	GW4090	GW4090C
	X	X	X	X	X	X	X
GW6090	GW6090DS	GW6090DSV	WP3000	WSB	WS8CAB	WS18	WS18CAB

